

## LMR 200 cable assembly, N m \* N f



### LMR200 Specification

Item	Specification
Cut off Frequency	DC~5.8GHz
Impedance	50 Ω
Weight	0.03 Kg / 1M
V.P.	84%
Peak Power	2.5 KW
Overall Diameter	4.95mm

### LMR200 Attenuation

Frequency	Attenuation
150 MHz	0.131dB/m
450 MHz	0.228dB/m
900 MHz	0.326dB/m
1800 MHz	0.466dB/m
2000 MHz	0.493dB/m
2500 MHz	0.554dB/m
5800 MHz	0.865dB/m

### Connector Selection Guide

	MMCX	MCX	SMA	SMB	BNC	TNC	N	Din
MMCX	X	X	O	O	O	O	O	X
MCX	X	X	O	O	O	O	O	X
SMA	O	O	O	O	O	O	O	X
SMB	O	O	O	O	O	O	O	X
BNC	O	O	O	O	O	O	O	X
TNC	O	O	O	O	O	O	O	X
N	O	O	O	O	O	O	O	X
DIN	X	X	X	X	X	X	X	X

## Item : CA/A, LMR200 N M \* N F

### N Electrical Specification

Item	Specification
Frequency range	DC ~ 5.8GHz
Impedance	50 Ω
V.S.W.R.	1.20 Max
Mating	500 Cycles Min
Operating Temperature	-45°C ~85°C

### N Material Specification

Item	Specification
Connector Body	Brass / Nickel or Tri-alloy Plating
Center contact	Brass, Beryllium / Gold Plating
Insulator	PTFE

### Drawing

